

# LFX

## DataSheet

### LITHIUM-ION BATTERY FIRE EXTINGUISHER RANGE

The LFX range has been specifically designed to tackle lithium-ion battery fires across a wide range of applications. In addition to primary fire risks, the LFX fluorine-free range of fire extinguishers also protect from secondary A-class fires that have been caused by the exploding batteries.



**COMMANDEREDGE**

FX-LI-003-MCF	
Agent	LFX
Capacity (litres)	3
Fire performance	Pending - 13A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	25 - 30
Cylinder	Lined steel
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE

FX-LI-006-MCF	
Agent	LFX
Capacity (litres)	6
Fire performance	Pending - 27A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	47 - 53
Cylinder	Lined steel
Approved certification	NTA 8133
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE

FX-LI-009-MCF	
Agent	LFX
Capacity (litres)	9
Fire performance	Pending - 34A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	72 - 78
Cylinder	Lined steel
Approved certification	NTA 8133
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE

#### PRODUCT CODE

FX-LI-003-MCF  
FX-LI-006-MCF  
FX-LI-009-MCF

#### PRODUCT GROUP

CommanderEDGE Extinguishers

#### DIMENSIONS (mm) (height x width x diameter)

FX-LI-003-MCF: 435 x 285 x 145  
FX-LI-006-MCF: 568 x 300 x 170  
FX-LI-009-MCF: 622 x 265 x 190

#### WEIGHT

FX-LI-003-MCF: 5.8kg  
FX-LI-006-MCF: 10kg  
FX-LI-009-MCF: 14.3kg

- Fluorine free foam concentrate
- 3ltr, 6ltr and 9ltr available
- Easy and ergonomic operation
- Economical maintenance and service

