

FC-178-002

Red Visual Indicator Only

General

The FC-178-002 is a RED, fire alarm Visual Indicating Device to be used with a wireless base FC-171-002.

The VID is quick and easy to install into the wireless base with a simple turn and lock mechanism.

The Range

The Fusion series consists of:

- Optical Smoke Detectors
- Multisensor Smoke Detectors
- A1R Heat Detectors
- CS Heat Detectors
- Sounders in red and white
- Combination Sounder VIDs and VADs
- Manual Call Points
- Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from its base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



Details

- For use with Fusion system
- Self-test fault monitoring
- Individual and group addressing
- Easy to install
- Proven technology

FC-178-002

Red Visual Indicator Only

Technical specifications

General

| | |
|--------------------|--------------------------|
| Wireless frequency | 868 MHz |
| Compatibility | Wireless base FC-171-002 |

Electrical

| | |
|-------------------|-----------------|
| Power supply type | Batteries |
| Batteries | Powered by Base |
| Operating voltage | 2.8 to 5 VDC |

VID

| | |
|--------|-----|
| Colour | RED |
|--------|-----|

Physical

| | |
|---------------------|---|
| Physical dimensions | 104 mm x 97.5 mm (Ø x H) - without base |
| Net weight | 205 g - without base |
| Colour | Red |
| Mounting type | Base mount |
| Mounting base | Wireless |

Environmental

| | |
|-----------------------|----------------------|
| Vandal proof | No |
| Operating temperature | -10°C to 55°C |
| Storage temperature | 5°C to 30°C |
| Relative humidity | < 95% non-condensing |
| Environment | Indoor |
| IP rating | IP54 |

Regulatory

| | |
|------------|-------------------------|
| Compliancy | CE, REACH, RoHS 2, WEEE |
|------------|-------------------------|



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 21 August 2023 - 16:54