



FC-323-WA2

Red, wall mount beacon only

The FireCell Wireless Beacon is quick and easy to install, offering individual addressing at the fire control panel. This device comprises of a sounder beacon and a wireless sounder base.

Works with FC-171-002 Red Wireless Sounder Base



Details

- 0.5 Hz / 1 Hz beacon flash selection
- Anti tamper locking mechanism
- Beacon EN54-23 coverage: W-3.1-11.3 / 396 m³
- Third party EN certified

FC-323-WA2

Red, wall mount beacon only

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	FC-171-002

Electrical

Power supply type	Batteries
Batteries	Powered by Radio Base

VAD

Colour	White Flash
Rating	W-3.1-11.3
Flash frequency	0.5 Hz / 1 Hz (selectable)

Physical

Physical dimensions	120 x 145 mm (Ø x D)
Net weight	0.65 kg
Colour	Red housing / white flash
Mounting type	Wall mount
Mounting position	Wall
Mounting base	Wireless

Environmental

Vandal proof	Yes
Operating temperature	-10 to 55 °C
Environment	Indoor

Regulatory

Compliance	CE
Certification	CPR
Standards	EN54-23



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 28 August 2024 - 10:16