

Ancillary Cancel Plate

ViAC-ACP-W



The ViAC-ACP-W Ancillary Cancel Plate is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

- Compact design
- BS 8300-2:2018 "Acknowledge" feature
- Flush or surface mounting
- Braille enhanced cancel button
- White polycarbonate

Overview

The ViAC-ACP-W Ancillary Cancel Plate is used where additional cancel buttons are required. The Assist Call emergency assistance alarm allows for 2 x standard cancel plates wired on a dedicated circuit, this is generally sufficient for most applications. However, in an accessible bedroom an additional cancel button may be required on the other side of the bed.

Installation

The cancel plate should be mounted at between 800mm to 1000mm.

The Ancillary Cancel plate should only be used as an additional cancel plate alongside a standard point since it does not have any audible or visible indication. Generally 2 x Ancillary Cancel plates can be added to a standard dedicated Assist Call ACA or ACB circuit. (Please check with Vox Ignis Technical).

Operation

When the alarm is activated, the system may be reset by pressing the ancillary cancel button, as mentioned previously the plate will not indicate or sound. Therefore there should be standard cancel or over door plates nearby for this purpose.

Technical Specification

Details	ViAC-ACP-W	
Physical		
Height	86mm	
Width	86mm	
Visible plate depth	12mm	
Weight	60g	
Material	White polycarbonate	
Part Numbers		
Ancillary Cancel Plate	ViAC-ACP-W	
Recommended Cables		
Type	Cores	Distance from panel/controller
PVC or fire rated*	2 core 1mm	500m
Cat5/6	1 x pair 0.22mm	50m
Standards Compliance		
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020	
LVD	EN IEC62368-1:2020 + A11:2020	
Product Family	BS 5839-9:2021 BS 8300-2:2018	

*If connected to a Refuge Point