

## Cancel Plate

ViAC-CNP-W



The ViAC-CNP-W Assist Call cancel plate is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

- Compact design
- BS 8300-2:2018 “Acknowledge” feature
- Blue indication
- Flush or surface mounting
- High volume sounder
- White polycarbonate
- Braille enhanced button

### Overview

The cancel plate allows for the assistance alarm to be cancelled.

#### Installation

The cancel button should be mounted in accordance with the requirements Building Regulations Document M (Access for the Disabled) and BS 8300-2:2018. The cancel button is finished in white polycarbonate with a blue indicator for the visual alarm and a high volume sounder.

For simplicity, all wiring is a standard two core cable, the wiring order of the plates is not fixed and therefore can be wired in any order to give flexibility in the installation routes. Each plate has two sets of two part terminals allowing simple cable connections.

There is a maximum number of 3 cancel plate and over door indicators on a single line.

#### Operation

When the alarm is activated or acknowledged, pressing the button on the cancel plate will cancel the alarm.

### Technical Specification

Details	ViAC-CNP-W	
<b>Physical</b>		
Height	86 mm	
Width	86 mm	
Visible plate depth	12 mm	
Weight	60 g	
Material	White polycarbonate	
<b>Part Numbers</b>		
Cancel Plate	ViAC-CNP-W	
<b>Recommended Cables</b>		
<b>Type</b>	<b>Cores</b>	<b>Distance from panel/controller</b>
PVC or fire rated*	2 core 1 mm	500 m
Cat5/6	1 x pair 0.22 mm	50 m
<b>Standards Compliance</b>		
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020	
LVD	EN IEC62368-1:2020 +A11:2020	
Product Family	BS 5839-9:2021 BS 8300-2:2018	

\*If connected to a Refuge Point