

## Pull Cord

ViAC-CPP-W



The ViAC-CPP-W Assist Call pull cord is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

- Compact design
- BS 8300-2:2018 “Acknowledge” feature
- Blue indication
- Flush or surface mounting
- 2.7 m red pull chord with 2 rings
- White polycarbonate

### Overview

The pull cord is used to activate the assistance alarm in the event of an emergency.

#### Installation

The pull cord should be mounted in accordance with the requirements Building Regulations Document M (Access for the Disabled) and BS 8300-2:2018. The pull cord is finished in white polycarbonate with a blue indicator for the visual alarm.

For simplicity, all wiring is a standard two core cable, the wiring order of the plates is not fixed and therefore can be wired in any order to give flexibility in the installation routes. Each plate has two sets of two part terminals allowing simple cable connections.

There is a maximum number of 6 pull cord on a single line, with the last one operated registering.

#### Operation

Pulling the cord will activate the alarm, it will then illuminate and sound to confirm the alarm state.

### Technical Specification

Details	ViAC-CPP-W	
<b>Physical</b>		
Height	86 mm	
Width	86 mm	
Visible plate depth	12 mm	
Weight	60 g	
Material	White polycarbonate	
<b>Part Numbers</b>		
Pull Cord	ViAC-CPP-W	
<b>Recommended Cables</b>		
<b>Type</b>	<b>Cores</b>	<b>Distance from panel/controller</b>
PVC or fire rated*	2 core 1 mm	500 m
Cat5/6	1 x pair 0.22 mm	50 m
<b>Standards Compliance</b>		
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020	
LVD	EN IEC62368-1:2020 +A11:2020	
Product Family	BS 5839-9:2021 BS 8300-2:2018	

\*If connected to a Refuge Point