

Over Door Indicator

ViAC-ODP-SS



The ViAC-ODP-SS Assist Call over door indicator is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

- Compact design
- BS 8300-2:2018 “Acknowledge” feature
- Blue indication
- Flush or surface mounting
- High volume sounder
- Blue polycarbonate with stainless steel fascia

Overview

The over door indicator gives a visual and audible indication of assistance alarm activation.

Installation

The over door indicator should be mounted in accordance with the requirements Building Regulations Document M (Access for the Disabled) and BS 8300-2:2018. The over door indicator is finished in blue polycarbonate with a stainless steel fascia, a blue indicator for the visual alarm and a high volume sounder.

For simplicity, all wiring is a standard two core cable, the wiring order of the plates is not fixed and therefore can be wired in any order to give flexibility in the installation routes. Each plate has two sets of two part terminals allowing simple cable connections.

For information about number of devices per line, refer to the AssistCall Installation Notes document.

Operation

When the alarm is activated the over door indicator will flash and play an alarm tone. Once the alarm is acknowledged the indication will turn solid blue and the sounder will emit a pair of beeps every 15 seconds.

Technical Specification

Details	ViAC-ODP-SS	
Physical		
Height	86 mm	
Width	86 mm	
Visible plate depth	12 mm	
Weight	60 g	
Material	Blue polycarbonate Stainless Steel	
Part Numbers		
Over Door Indicator	ViAC-ODP-SS	
Recommended Cables		
Type	Cores	Distance from panel/controller
PVC or fire rated*	2 core 1 mm	500 m
Cat5/6	1 x pair 0.22 mm	50 m
Standards Compliance		
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020	
LVD	EN IEC62368-1:2020 +A11:2020	
Product Family	BS 5839-9:2021 BS 8300-2:2018	

*If connected to a Refuge Point