

Ceiling VAD

ViUV-CV-UL-EU



Unicorn Voice is a unique distributed wall-mounted, panel based voice alarm and fire telephone solution that is compliant to EN54-16.

- Certified to EN 54-23:2013
- Synchronised operation
- Low current
- Compatible with Unicorn Voice
- 18V DC to 30 V DC-
- Single UK Mounting
- 1st fix termination plate.
- 5x 20 mm

Overview

These VADs have specifically been designed to complement the Unicorn Voice PAVA range. The VADs feature low current and high performance.

Matching VAD/speaker performance

There are many applications which require VADs (Visual Alarm Devices) to supplement the alarm system to meet the requirements of the Equality Act and Building Regulations.

These VADS have specifically been designed to complement the Unicorn Voice range of loudspeakers. They have matching coverage and importantly are fully synchronised so all VADs will be operating together.

Technical Specification

Details	ViUV-CV-UL-EU
VAD specification	
VAD classification	C3-6
Operating voltage	18 to 30 VDC
Current consumption	12 mA
Frequency range	0.5 HZ
Environmental	
Operating temp	-10°C to 55°C
Humidity range	0 to 80% non-condensing
Ingress Protection	IP21C
MECHANICAL	
Material	Polycarbonate
Colour	White RAL 9016
Dimensions H x W mm	86 x 86
Net Weight	270g

Ordering Information

Part Code	Description
Accessories	
ViUV-CV-UL-EU	Ceiling VAD