

Specifications



Eaton SD-LTE

Eaton Speech dialler, Mobile networks, Voice, SMS

General specifications

PRODUCT NAME	Eaton speech dialler
CATALOG NUMBER	SD-LTE
EAN	5060096858485
PRODUCT LENGTH/DEPTH	30 mm
PRODUCT HEIGHT	115 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	CE marking
CERTIFICATIONS	CE



Powering Business Worldwide

Product specifications

NUMBER OF INPUTS - MAX	8
SUPPLY	12 VDC
TRANSISTOR OUTPUTS	4
ATS RATING	Not applicable
CONTACTS	10
CURRENT - MAX	170 mA
CURRENT NORMAL	50 mA
EN 50131 GRADE	Not applicable
ENCLOSURE COLOUR	White
ENCLOSURE MATERIAL	Plastic
ENVIRONMENTAL CLASS	Class II
INTERNAL AERIAL	Not applicable
LISTEN IN	Yes
MAXIMUM NUMBER OF INPUTS	8
MESSAGES - SMS	8
MESSAGES - SPEECH	8
MOUNTING	Surface
NUMBER OF RELAY OUTPUTS	Not applicable
NUMBER OF TRANSISTOR OUTPUTS	4
OPERATING TEMPERATURE - MAX	55 °C
OPERATING TEMPERATURE - MIN	-10 °C
TYPE OF COMMUNICATOR	Communicator
PROGRAMMING DISPLAY	LCD
RADIO FREQUENCY	850/900/1800/1900MHz
REMOTE ACCESS	Yes
SUPPLY - MAX	28 VDC
SUPPLY - MIN	10.5 VDC
TALK BACK	Yes
TEMPERATURE SENSOR	Yes
TYPE OF CURRENT	DC
VDS CLASS	None
WIRED INPUT TYPE	CC
WITH HOUSING	Yes
WITH POWER ADAPTOR	No

Resources

BROCHURES	Scantronic security systems - Product range brochure
CATALOGUES	SD3 and SD-GSM Speech dalliers - Datasheet
	SD1 and TSD2 Speech dalliers - Datasheet
	SD1 EC Speech dalliers - Declaration of conformity
	SD GSM EC Speech dallier - Declaration of conformity
	SD3 EC Speech dalliers - Declaration of conformity

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.