

Exitguard

EX125i

The **Exitguard EX125i** is designed specifically for integration with Grade 2 EN50131 intruder alarm systems.

Selectable resistors (1k + 1k or 4k7/4k7) ensure compatibility with intruder alarm panels such as Honeywell and Aritech. The unit communicates alarms and faults to the main system via a supervised loop with separate alarm output. It also features auto sounder reduction to minimise noise after a preset period, with the sounder only restarting if the door is reopened.

The **Bleep In Off (BIO)** function provides an audible and visual alert when the unit is turned off, reducing the chances of it being forgotten.

Specification	EX125i
Audible Alarm Indication	Yes
Selectable Tones	Yes
Visual Alarm Indication	Yes
Enclosure	ABS
Sounder Output @ 1m	108 dB
Supervised Loop On/Off monitor	Yes
Supervised Loop Alarm Output	Yes
Keyswitch Control	Yes
Unit Tamper	Yes
Compatibility	All Key Intruder Panels
Dimensions	175 x 125 x 60 mm
Replacement Key Barrels	Yes
Country of Manufacture	United Kingdom
Approvals	UKCA and CE marked, ROHS compliant

Benefits and Features

- Designed for grade 2 intruder systems
- High power piezo sounder 108dB @1m
- Selectable alarm tones
- Visual alarm indication
- Keyswitch control with random key numbers
- Audible / visual warning when turned off (BIO)
- Supervised loop for On/Off monitor & separate Alarm output
- Safe Set to minimises false alarms
- Tamper switch
- Selectable resistor values for outputs
- Simple function change by Internal Jumpers
- Compatible with key panel manufacturers

All Exitguards are supplied with fixings, door contact, 1 metre of cable and a door warning sign.



Dimensions (mm)

