

# ActiV Conventional Base Voice Sounder

Part No. **BF454C/CC/W**

**C-TEC  
Manufactured**



## Overview

- Superb sound intelligibility.
- Choose from two evacuation voice messages and four evacuation alarm tones (your selected evacuation message will be preceded by the selected tone).
- Alarm Current at 30Vdc = 10mA.
- Alarm Current at 18Vdc = 8mA.
- Optional BF330CTLIDW white or BF330CTLIDR red cap available for stand-alone use.
- Supplied with a BF431QCP quick connect plate and detector spur wires.
- IP21C rated.

## Technical Specifications

Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be ceiling mounted - either stand-alone with a red or white cap or as part of a stacked Sounder/Detector Base combination.
Supply/operating voltage	18 to 30V DC.
Alarm current	At 30Vdc: 10mA; At 18Vdc: 8mA.
Product dimensions (mm)	122mm diameter x 46mm deep (not including optional detector and base).
IP Rating	IP21C (Type A).
Weight	160g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).
Notes	Choose from 2 evacuation voice messages and 4 evacuation tones. Note all of these have an associated alert tone/message, the activation of which requires additional wiring and control functionality